

Home | Login | Logout | Access Information | Alerts | Purchase History | Cart | Sitemap | Help

**IEEE Xplore**  
DIGITAL LIBRARY

Welcome Politehnica Timisoara

**IEEE**

Abstract BROWSE SEARCH IEEE XPLORE GUIDE SUPPORT

View Search Results e-mail printer friendly

**The AbstractPlus record may not be viewed.**  
You are viewing the Abstract record because the article you selected is not part of your subscription.

**Login**  
Username:   
Password:


[» Forgot your password?](#)

Please remember to log out when you have finished your session.

**You must log in to access:**

- Advanced or Author Search
- CrossRef Search
- AbstractPlus Records
- Full Text PDF
- Full Text HTML

**Access this document**

 Full Text: [PDF](#) (7916 KB)

[» Buy this document now](#)

[» Learn more about subscription options](#)

[» Learn more about purchasing articles and standards](#)

**Rights and Permissions>**  
[» Learn More](#)

**Download this citation**  
Available to subscribers and IEEE members.

[View Search Results](#)

---

## Monitoring Serial Communications in Microcontroller Based Embedded Systems

Popa, M. Popa, A.S. Cretu, V. **Micea, M.**  
Comput. & Software Eng. Dept., "Politehnica" Univ. of Timisoara  
This paper appears in: [Computer Engineering and Systems, The 2006 International Conference on](#)  
Publication Date: 5-7 Nov. 2006  
On page(s): 56 - 61  
Location: Cairo  
ISBN: 1-4244-0271-9  
Digital Object Identifier: 10.1109/ICCES.2006.320425  
Current Version Published: 2007-02-26

---

**Abstract**  
More and more microcontrollers are embedded in a large area of products from industrial to domestic domains. A good example is the automobile, a modern one containing tens of microcontrollers. As their number increased the communication between them became necessary. The serial solution was preferred and a lot of serial buses and protocols were developed optimizing different parameters of the communication. Several examples are: RS232, LIN, SPI, CAN and so on. Monitoring serial communications is necessary in R&D phase, e.g. for creating virtual transfer partners, and in testing and debugging phases. The paper describes a message based monitoring tool for the RS232 bus and monitoring tools for the LIN and SPI buses. Many microcontrollers contain the LIN and SPI buses and almost all of them include the RS232 bus. The created tools work in passive mode, monitoring the transfers and sending the data to a PC or in active mode (only for the LIN bus), interfering in the communication and sending headers, responses or injecting typical errors

---

**Index Terms**  
Available to subscribers and IEEE members.

---


**References**  
Available to subscribers and IEEE members.

---

**Citing Documents**  
Available to subscribers and IEEE members.

---

[Help](#) [Contact Us](#) [Privacy & Security](#) [IEEE.org](#)

Indexed by 

© Copyright 2010 IEEE – All Rights Reserved