# ECP Standard Parallel Interface for DSP56300 Devices

# **Application Note**

by

Mihai V. Micea Dan Chiciudean and Lucian Muntean

> AN2085/D Rev. 0, 11/2000

© Freescale Semiconductor, Inc., 2004. All rights reserved.



For More Information On This Go to: www.freescale

**Freescale Semiconductor, Inc.** 

#### How to Reach Us:

#### Home Page:

www.freescale.com

E-mail: support@freescale.com

#### USA/Europe or Locations Not Listed:

Freescale Semiconductor Technical Information Center, CH370 1300 N. Alma School Road Chandler, Arizona 85224 +1-800-521-6274 or +1-480-768-2130 support@freescale.com

#### Europe, Middle East, and Africa:

Freescale Halbleiter Deutschland GmbH Technical Information Center Schatzbogen 7 81829 Muenchen, Germany +44 1296 380 456 (English) +46 8 52200080 (English) +49 89 92103 559 (German) +33 1 69 35 48 48 (French) support@freescale.com

#### Japan:

Semiconductor, Inc

**Besca** 

Freescale Semiconductor Japan Ltd. Headquarters ARCO Tower 15F 1-8-1, Shimo-Meguro, Meguro-ku, Tokyo 153-0064 Japan 0120 191014 or +81 3 5437 9125 support.japan@freescale.com

#### Asia/Pacific:

Freescale Semiconductor Hong Kong Ltd. Technical Information Center 2 Dai King Street Tai Po Industrial Estate Tai Po, N.T., Hong Kong +800 2666 8080 support.asia@freescale.com

#### For Literature Requests Only:

Freescale Semiconductor Literature Distribution Center P.O. Box 5405 Denver, Colorado 80217 1-800-441-2447 or 303-675-2140 Fax: 303-675-2150 LDCForFreescaleSemiconductor@hibbertgroup.com Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document. Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

#### For More Information On This Product, Go to: www.freescale.com

# **Abstract and Contents**

Semiconductor, Inc.

đ

reescal

The data communication between the DSP and a host computer is one of the important issues in designing DSP-based systems directly connected to PCs which are commonly used as process controllers or as interactive user interfaces. This application note proposes the implementation of a high-performance, yet relatively simple, parallel data communication protocol for a DSP connected to a PC.

This document focuses on the implementation of the Extended Capabilities Port (ECP) parallel communication standard on the DSP56300 family processors.

Specific ECP communication protocols are described along with the characteristic hardware and software implementation details, both on the DSP and on the PC side. The performance evaluation routines designed for the ECP data link are also presented, along with the corresponding results and conclusions.

1	Introduction	1
2	DSP-Host Communication Tradeoffs	1
3	ECP Standard Specifications	2
3.1 3.2 3.2.1 3.2.2 3.2.3 3.2.3 3.2.4 3.3	ECP Hardware Description. ECP Handshaking Protocols. ECP Forward Data Cycle. ECP Forward Command Cycle. ECP Reverse Data Cycle . ECP Reverse Command Cycle . ECP Reverse Command Cycle .	2 3 4 5 6 6
4	ECP Interface Implementation—Hardware	8
5	ECP Interface Implementation—Software	9
5.1 5.1.1 5.1.2 5.1.3 5.2	Implementation on the DSP Side       Initialization         Initialization       1         Forward Data       1         Reverse Data       1         ECP Programming on the Host Side       1	9 9 0 2 4
6	Performance Evaluation of the ECP Interface	6
6.1 6.2	Single-Byte Transmission1Buffered Transmission1	6 7
7	Boosting Performance with a DMA Controller	8

8	Conclusion	20
9	About the Authors	21
10	References	21

# 1 Introduction

Semiconductor, Inc

1

eescal

An important set of real-life digital signal processing applications involves a host computer functioning as a system controller or interactive graphical user interface. In these applications, reliable, high-speed data communication between the DSP and the host computer is an important design and implementation issue.

This document describes the implementation of a high-performance, yet relatively simple, parallel data communication protocol for a DSP connected to a PC. The paper focuses on the implementation of the Extended Capabilities Port (ECP) parallel communication standard on the DSP56300 family processors. Specific ECP communication protocols are described, as well as hardware and software implementation details for both the DSP and the PC. Performance evaluation routines designed for the ECP data link are also presented, along with corresponding results and conclusions.

Details of the ECP standard can be found in the Microsoft document, *Extended Capabilities Port: Specifications*, Revision 1.06.

# 2 DSP-Host Communication Tradeoffs

The DSP56300 family features various data communication interfaces, suitable for a large variety of system interconnections, through its built-in peripheral ports.

The Serial Communication Interface (SCI) provides a full-duplex port for serial data transfers. Using three dedicated signals (Data Transmit, Data Receive, and Serial Clock), this interface supports industry-standard asynchronous bit rates and protocols up to 115200 bps, as well as high-speed synchronous data transmission up to 8.25 Mbps for a 66 MHz clock. The primary disadvantage of a SCI-based connection with a host computer is that the maximum data transfer rate is limited to 115200 bps by the computer's serial interface. Another disadvantage is that many DSP-based evaluation modules use the DSP serial port for code development and debugging, making it difficult to develop a DSP program that can initiate serial data transactions autonomously with a host computer.

For high-performance parallel data transfers, the DSP56300 family provides a full-duplex, double-buffered parallel port called the Host Interface. This interface is either 8-bits or 32-bits wide, depending on the particular DSP device selected. The HI08 or HI32 can connect directly to the data bus of a host processor or computer with minimal glue logic, allowing direct data links to microcontrollers such as the Freescale HC11 or the Intel 8051 family, as well as to microprocessors such as the Freescale 68k family or Intel x86 family. The Host Interface can easily connect with the high-speed ISA or PCI bus on a PC to form a communication channel that is substantially faster than a serial connection (up to 16 MBps for the ISA bus, for example). However, this solution requires a very close physical connection, which drastically reduces overall system flexibility.

A good compromise between maximum data transfer speed and system flexibility is the parallel cable interconnection. The standard PC protocol for high-performance parallel communication is the Extended Capabilities Port (ECP). This document describes the hardware and software implementation of the ECP Standard with the HI08 port of a DSP56300 family device.

# 3 ECP Standard Specifications

The Extended Capabilities Port is a fast, bidirectional parallel interface developed by Microsoft and Hewlett-Packard. It is backward-compatible with the existing PC standard parallel port (SPP) configurations, using the existing parallel connectors and cables.

Pre-existing parallel communication methods utilized a wide variety of hardware and software interfaces, each with unique and incompatible signaling schemes. The ECP standard was developed to provide a standard, open path for communications between computers and more intelligent printers and peripherals. The availability of this standard bidirectional protocol encourages the development of new peripherals that can return both data and status to the host computer.

The ECP protocol generates handshake signals identical to those of the Extended Parallel Port (EPP), and runs at the same speed as EPP. It also supports Run Length Encoding (RLE) to achieve data compression ratios up to 64:1.

In summary, the ECP provides the following features:

- High performance half-duplex forward and reverse channel
- Interlocked handshake for fast, reliable data transfer
- Optional single-byte RLE compression for improved throughput
- Channel addressing for low-cost peripherals
- Active output drivers
- Adaptive signal timing
- Peer-to-peer capability

Semiconductor, Inc.

đ

eescal

The ECP provides three operational modes for compatibility with various systems:

- **Compatible mode**—asynchronous, byte-wide forward channel (host-to-peripheral), parallel port interface. Data and status lines are used according to the original SPP and EPP definitions.
- **Nibble mode**—asynchronous, byte-wide reverse channel (peripheral-to-host), parallel port compatible with all existing PC hosts. Data bytes are transmitted as two sequential 4-bit nibbles using four peripheral-to-host status lines.
- **Byte mode**—asynchronous, byte-wide reverse channel using the eight data lines of the interface for data and the control/status lines for handshaking, compatible with IBM PS/2 hosts.

In addition, the ECP offers:

• **ECP mode**—fast bidirectional channel, with or without RLE compression. This mode requires custom hardware.

# 3.1 ECP Hardware Description

The Extended Capabilities Port uses the industry-standard DB25 connector and is backward-compatible with the SPP and EPP parallel standards. When the ECP operates in SPP or EPP mode, the data and handshake lines operate according to the SPP and EPP definitions.

When the port operates in ECP mode, each of the DB25 connector pins has a unique function, as listed in Table 1.

Pin	SPP Signal	ECP Signal	Input/ Output	Function
1	Strobe	HostCLK	Output	A low on this line indicates valid data at the host. When this pin is de-asserted, the +ve clock edge should be used to shift the data into the peripheral.
2–9	Data 0–7	Data 0–7	I/O	Bidirectional data bus
10	Ack	PeriphCLK	Input	A low on this line indicates valid data at the peripheral. When this pin is deasserted, the +ve clock edge should be used to shift the data into the host.
11	Busy	PeriphAck	Input	In reverse channel operation, a high on this pin indicates a data cycle, while a low indicates a command cycle. In forward channel operation, the pin functions as PeriphAck.
12	Paper Out / End	nAckReverse	Input	The peripheral pulls this pin low to acknowledge a reverse request.
13	Select	X-Flag	Input	Extensibility Flag
14	Auto Linefeed	Host Ack	Output	In forward channel operation, a high on this pin indicates a data cycle, while a low indicates a command cycle. In reverse channel operation, the pin functions as HostAck.
15	Error / Fault	PeriphRequest	Input	The peripheral pulls this pin low to indicate that reverse data is available.
16	Initialize	nReverseRequest	Output	This pin is pulled low to indicate that data is in the reverse direction.
17	Select Printer	1284 Active	Output	The host pulls this pin high to indicate 1284 transfer mode, and pulls the pin low to terminate.
18–25	Ground	Ground	GND	Ground

### Table 1. Pin Assignments for Extended Capabilities Parallel Port Connector

## 3.2 ECP Handshaking Protocols

The ECP can be fully implemented by hardware with custom parallel communication controllers. It can be implemented in software as well.

The ECP handshaking protocol features the following four cycles:

• Forward Data

Semiconductor, Inc.

đ

reescal

L.

- Reverse Data
- Forward Command
- Reverse Command

### 3.2.1 ECP Forward Data Cycle

In the forward data cycle, the host sends a single byte of compressed data to the peripheral. This cycle consists of six steps:

- 1. Host places data on data lines.
- 2. Host asserts HostAck to indicate the start of a data cycle.
- 3. Host asserts HostClk to low to indicate valid data.
- 4. Peripheral asserts PeriphAck to acknowledge valid.
- 5. Host deasserts HostClk high. The +ve edge is used to shift data into the peripheral.
- 6. Peripheral de-asserts PeriphAck to acknowledge receiving the byte.

These steps are illustrated in Figure 1.

Semiconductor, Inc.

eesca



Figure 1. ECP Forward Data Cycle

### 3.2.2 ECP Forward Command Cycle

In the forward command cycle, the host sends a channel address to the peripheral. This cycle consists of six steps:

- 1. Host places data on data lines.
- 2. Host deasserts HostAck to indicate the start of a command cycle.
- 3. Host asserts HostClk low to indicate valid data.
- 4. Peripheral asserts PeriphAck to acknowledge valid data.
- 5. Host deasserts HostClk high. The +ve edge is used to shift data into the peripheral.
- 6. Peripheral deasserts PeriphAck to acknowledge receiving the byte.

These steps are illustrated in Figure 2.





### 3.2.3 ECP Reverse Data Cycle

In the reverse data cycle, the peripheral sends a single byte of data to the host. There are eight steps specified for the reverse data cycle:

- 1. Host sets nReverseRequest Low to request a reverse channel.
- 2. Peripheral asserts nAckReverse low to acknowledge reverse channel request.
- 3. Peripheral places data on data lines.
- 4. Peripheral pulls PeriphAck high to select data cycle.
- 5. Peripheral pulls PeriphClk low to indicate that valid data is present.
- 6. Host pulls HostAck high to acknowledge that valid data is present.
- 7. Peripheral pulls PeriphClk high. The +ve edge is used to shift data into the host.
- 8. Host deasserts HostAck low to acknowledgment receipt of the byte.

These steps are illustrated in Figure 3.

Semiconductor, Inc

٩

reescal





### ECP Standard Specifications For More Information On This Product, Go to: www.freescale.com

### 3.2.4 ECP Reverse Command Cycle

In the reverse command cycle, the peripheral sends a channel address to the host. There are eight steps specified for the reverse command cycle:

- 1. Host sets nReverseRequest Low to request a reverse channel.
- 2. Peripheral asserts nAckReverse low to acknowledge reverse channel request.
- 3. Peripheral places data on data lines.
- 4. Peripheral pulls PeriphAck low to select command cycle.
- 5. Peripheral pulls PeriphClk low to indicate that valid data is present.
- 6. Host pulls HostAck high to acknowledge that valid data is present.
- 7. Peripheral pulls PeriphClk high. The +ve edge is used to shift data into the host.
- 8. Host deasserts HostAck low to acknowledgment receipt of the byte.

These steps are illustrated in Figure 4.

Semiconductor, Inc.

٩

eescal



Figure 4. ECP Reverse Command Cycle

# 3.3 ECP Software Registers

The software registers implemented in a standard PC on the host side of the ECP interface are listed in Table 2. The first 3 registers are identical to those in the Standard Parallel Port.

Address	Port Name	Read/Write	Description
Base + 0	Data (SPP)	Read/Write	Standard parallel port data register. Writing to this register in SPP mode drives data on the parallel port data lines. In all other modes the drivers can be tri-stated by setting the direction bit in the Control Register.
	ECP Address FIFO (ECP mode)	Read/Write	Data written to this address is placed in the FIFO and tagged as ECP Address/RLE. ECP port hardware transmits the byte to the peripheral automatically.
Base + 1	Status Register	Read	Reflects the inputs on the parallel port interface.
Base + 2	Control Register	Read/Write	Directly controls several output signals, sets the direc- tion of communication, and enables an interrupt on the rising edge.
Base + 400h	Data FIFO (Parallel Port FIFO Mode)	Read/Write	In Parallel Port FIFO Mode, any data written to the Data FIFO is sent to the peripheral using the SPP handshake; hardware generates the handshaking required.
	Data FIFO (ECP Mode)	Read/Write	When data direction is 0 (output to peripheral), bytes written or DMAed from the system to this FIFO are transmitted to the peripheral by hardware handshake using the ECP parallel port protocol. When data direc- tion is 1 (input from peripheral), bytes from the periph- eral are read into this FIFO under automatic hardware handshake from ECP.
	Test FIFO (Test Mode)	Read/Write	Data can be read, written, or DMAed to or from the system to this FIFO in any direction; data is not trans- mitted to the parallel port lines using a hardware pro- tocol handshake but can be displayed on the parallel port data lines.
	Configuration Register A (Configuration Mode)	Read/Write	Indicates if the card generates level- or edge-trig- gered interrupts and the bus widths within the card, and determines if there are any bytes left in the FIFO. Configuration Register A is accessible only when the ECP Port is in Configuration Mode.
Base + 401h	Configuration Register B (Configuration Mode)	Read/Write	Selects compression option (RLE) for outgoing data, returns the status of the IRQ pin, IRQ assignment and DMA Channel assignment. Configuration Register B is accessible only when the ECP Port is in Configura- tion Mode.
Base + 402h	Extended Control Register	Read/Write	Configures the ECP mode and returns the status of the ECP FIFO. Modes of operation include: • Standard Mode • Byte / PS/2 Mode • Parallel Port FIFO Mode • ECP FIFO Mode • EPP Mode • FIFO Test Mode • Configuration Mode

### Table 2. ECP Registers

#### ECP Standard Specifications For More Information On This Product, Go to: www.freescale.com

#### **ECP Interface Implementation—Hardware** 4

The hardware connection between the PC and DSP is a standard DB25 parallel cable. On the host side, the cable connects to the standard parallel port, configured for the ECP protocol. On the DSP side, the cable connects to a male DB25 header, which is directly connected to the HI08 port as illustrated in Figure 5.





Because of an order from the United States International Trade Commission, BGA-packaged product lines and part numbers indicated here currently are not

available from Freescale for import or sale in the United States prior to September 2010: DSP56303

In this implementation, all HI08 signals are configured as General Purpose I/O lines (GPIO) during the ECP initialization routine for the DSP. The Host Interface data lines (HAD0–HAD7) are assigned to the ECP data bus (D0–D7). The ECP handshake signals are connected to the HI08 port as shown in Table 3.

ECP Signal	Direction	HI08 Signal
HostClk		HAS/A0
Data 0–7	<b>~</b>	HAD0-HAD7
PeriphClk	-	HA8/A1
PeriphAck	-	HA9/A2
nAckReverse	-	HRW/RD
HostAck	>	HDS/WR
nReverseRequest		HCS/A10

					_
l able 3.	ECP to	HI08	Pin	Assio	Inments

In some cases, the electrical signal coupling between the DSP and the host computer may require voltage level shifters to accommodate the 3.3V DSP56300 family I/O port voltage levels and the 5V (TTL) parallel interface signals of the host computer. Tests run with the ECP implementation on the DSP56303 issued satisfactory results without such voltage level interface buffers, but special care must be taken with each DSP56300 family device.

# 5 ECP Interface Implementation—Software

The ECP handshake signals required to control data transactions between the DSP and the host computer can be generated either in hardware, using a customized ECP controller, or in software. This section describes the latter approach for the DSP side, in which software polls the HI08 port to generate the ECP handshake signals. The host side employs a hardware controller, but does require some initialization software which is also described.

# 5.1 Implementation on the DSP Side

The ECP standard defines four main protocol phases: ECP forward data and reverse data cycles for data transactions, and ECP forward command and reverse command cycles to indicate single-byte data compression or channel address. This section presents DSP software for the two data cycles, which are the basic requirement for the ECP communication, as well as an initialization routine.

### 5.1.1 Initialization

Semiconductor, Inc.

reescale

The DSP initialization routine includes:

- Configuring the HI08 port as GPIO
- Setting the direction of each line used for handshaking
- Generating the correct logical levels on the output lines
- Initializing the HI08 lines that connect to the ECP data bus as inputs

The code for this routine is presented in Example 1.

hpcr hddr hdr HOSTCLK PERIPHCLK PERIPHACK nACKREVERSE HOSTACK nREVERSEREQU	equ equ EQU EQU EQU EQU EQU EQU EST EQU	\$ffffc4 \$ffffc8 \$ffffc9 8 9 10 11 12 13	<pre>;Host Port Control Register Address ;Host Data Direction Register address ;Host Data Register address ;The next 6 equates are used for ;;addressing the handshaking lines in ;;Host Data Register</pre>
init_ecp bset bclr bset bset bclr bset bclr bclr bclr bclr ts	<pre>#0,x:hpcr #HOSTCLK,x:h #PERIPHCLK,x PERIPHCLK,x: PERIPHACK,x: PERIPHACK,x: nACKREVERSE, nACKREVERSE, HOSTACK,x:hd nREVERSEREQU line_in</pre>	ddr ::hddr hdr hdr hdr x:hddr x:hdr dr EST,x:hddr	
line_in move and move rts	x:hddr,a #\$ff00,a a,x:hddr		;Configures the 8 data lines ;;as inputs

#### Example 1. ECP Initialization Routine

### 5.1.2 Forward Data

Semiconductor, Inc.

Freescale

For the ECP forward data cycle, the DSP implements a read routine, which is called each time a byte is to be transferred from the host to the DSP. Figure 6 is a flowchart of the read routine.



Figure 6. ECP Read Routine Flowchart

In accordance with ECP specifications, the read routine performs a blocking scan of the nReverseRequest ('data direction') and HostClk ('data valid') lines. If the host pulls the data direction line low, indicating a host request to read data from the DSP, a "time-out" condition occurs; the program exits the read routine and goes to the write routine. Otherwise, the read routine waits for a byte to be sent by the host, indicated by a high on the HostClk line.

The code for the read routine is given in Example 2 on page 12.

Semiconductor, Inc.

Freescale

Example 2. ECP Read Routine

read	jclr bset	<pre>#nREVERSEREQUEST,x:hdr,* #PERIPHCLK,x:hdr</pre>	;Wait for nRevReq line to ;;go high and then sets ;;the PeriphClk line.
ral	jclr	<pre>#nREVERSEREQUEST,x:hdr,time_out_;</pre>	rd ;Check if nRevReq is low ;;and if so, a time out ;;condition occured.
	jset	#HOSTCLK,x:hdr,rdl	; If HostClk is low then ; ; sets PerphClk and
rd2	bset	<pre>#PERIPHACK,x:hdr</pre>	;;continue.
	jclr jclr bsr	<pre>#nREVERSEREQUEST,x:hdr,read_end #HOSTCLK,x:hdr,rd2 data_in</pre>	;Wait for HostClk to go ;;high and then samples ;;the data bus.
time_c read_e	out_rd bclr end rts	#PERIPHACK,x:hdr	Reset the PeripAck line
data_i	n move extrac rts	x:hdr,a0 tu #\$8000,a,a	;Get one byte from data ;;bus and store it in a0.

### 5.1.3 Reverse Data

For the ECP reverse data cycle, the DSP implements a write routine in accordance with the corresponding ECP protocol specifications. Figure 7 is a flowchart of the read routine.

Because of an order from the United States International Trade Commission, BGA-packaged product lines and part numbers indicated here currently are not available from Freescale for import or sale in the United States prior to September 2010: DSP56303



Semiconductor, Inc.

Freescale

Figure 7. ECP Write Routine Flowchart

The write routine performs a non-blocking scan on the nReverseRequest ('data direction') handshake line. If the line is high, indicating that the host is in the Forward Data phase of ECP operation and is not ready to receive the data byte from the DSP, the program exits the write routine and goes to the read routine. Otherwise, the write routine sends the byte out on the ECP data bus.

The code for the write routine is given in Example 3.

|--|

write			
	jset bclr	<pre>#nREVERSEREQUEST,x:hdr,write_end #nACKREVERSE,x:hdr</pre>	<pre>;If nRevReq line is low, ;;exit from write routine,</pre>
	bsr da	ta_out	;;else reset nAckRev, ;;output the data on data ;;lines.
	bset bclr	#PERIPHACK,x:hdr #PERIPHCLK,x:hdr	;Assert PeriphAck, ;ide assert PeripClk.
wrl	jset	<pre>#nREVERSEREQUEST,x:hdr,time_out_v #UOSTACK</pre>	vr Wait for Wastley to so
	bset	#PERIPHCLK, x:hdr	;;high and set PeripClk.
WL Z	jset	<pre>#nREVERSEREQUEST,x:hdr,time_out_v</pre>	vr
	jset	#HOSTACK,x:hdr,wr2	;Wait for HostAck to go ;;low.
time_c	ut_wr		
	bsr li	ne_in	;Switch the data bus ;;direction to in.
	bclr bset	#PERIPHACK,x:hdr #nACKREVERSE x:hdr	Reset PeriphAck and
write_	end rts		,, bee menter.
data_o	ut		
	move	a0,x0	;Take the least ;;significant byte from
	move	x:hdr,a0	;;a0 and send it,
	insert	\$8000,x0,a	;;without modifying
	move	a0,x:hdr	;;the most significant
	move	x:hddr,al	;;byte from Host Data
	or	\$tt,a	;;Register.
	movev rts	al,x:nddr	

# 5.2 ECP Programming on the Host Side

The host computer generates the ECP communication protocol with a hardware controller on the motherboard, so the only programming requirements are proper ECP controller initialization and a pair of routines for data transmission and reception between the ECP port and the user application.

Because of an order from the United States International Trade Commission, BGA-packaged product lines and part numbers indicated here currently are not available from Freescale for import or sale in the United States prior to September 2010: DSP56303

Example 4 presents all the initialization routines needed for data communication through the host ECP port. User applications should call these functions in a similar manner to the communication evaluation program described in Section 6, "Performance Evaluation of the ECP Interface," on page 16.

#### ECP Standard Parallel Interface for DSP56300 Devices For More Information On This Product, Go to: www.freescale.com

### Example 4. Host ECP Initialization Routines

```
#define b_addr 0x378
unsigned char Read_cnfg(int reg){
             return inb(b_addr+0x400+reg);
}
void Write_cnfg(int reg,unsigned char x){
             outb(x,b_addr+0x400+reg);
}
Write_cnfgA(unsigned char x){
             Write_cnfg(0,x);
}
Write_cnfgB(unsigned char x){
             Write_cnfg(1,x);
}
unsigned char Read_cnfgB(void){
             return Read_cnfg(1);
}
//Initialize the parallel port in ECP mode.
void init_ecp(){
             outb(0x34,b addr+0x402);
             outb(0xf4,b_addr+0x402);
             Write_cnfgA(0x14);
             Write_cnfgB(Read_cnfgB()&0x7f);
}
//Place the ECP in Forward phase.
void init_write(){
             unsigned char x;
             outb(0x34,b addr+0x402);
             outb(inb(b_addr+2)&0x0C,b_addr+2);
             x=inb(b_addr+2);
             outb(0x34,b_addr+0x402);
             outb(0x75,b_addr+0x402);
             outb(x|4,b_addr+2);
             while ((!inb(b_addr+1))&(1<<6));</pre>
}
//Place the ECP in Reverse phase.
void init_read(){
             unsigned char x;
             outb(0x34,b_addr+0x402);
             outb(inb(b_addr+2)|0x20,b_addr+2);
             x=inb(b_addr+2);
             outb(0x75,b addr+0x402);
             outb(x&0xfb,b_addr+2);
             while((!inb(b_addr+1))&(1<<5));</pre>
}
//Test if ECP FIFO is empty.
int fifo_empty(){
             return (inb(b_addr+0x402)&1);
}
//Test if ECP FIFO is full.
int fifo_full(){
             return (inb(b_addr+0x402)&2);
```

Semiconductor, Inc.

٩

eescal

#### ECP Interface Implementation—Software For More Information On This Product, Go to: www.freescale.com

# 6 Performance Evaluation of the ECP Interface

This section describes a time-based, data counting performance evaluation program for the ECP interface, and presents results for forward and reverse data transfer modes.

To evaluate data communication performance through the ECP interface, programs must be developed for both the host and the DSP. The performance parameters of primary concern are the occurrence of errors during the transfer and the data transfer rate. To determine the maximum transfer rate of the proposed ECP implementation, a large amount of data must be sent through the parallel link with minimal interference from other activities during the data transfer.

# 6.1 Single-Byte Transmission

A first approach is to transmit one byte at a time. For reverse mode, the ECP test routine on the DSP side simply transmits a byte of data on the ECP in an infinite loop, incrementing the value sent after each transferred byte.

Example 5 lists the reverse mode ECP test routine on the DSP.

ECP_te	est		Test the ECP Reverse phase
again	bsr	init_ecp	;Initialize the HIU8
	move	b,a	
	jsr	write	;Write a byte (from a0) to the host
	inc	b	;Increment the value
	jmp	again	;Infinite loop

A similar algorithm is used for the ECP forward mode.

Semiconductor, Inc.

đ

eescal

The actual ECP performance evaluation program resides on the host computer. The host routine measures the time it takes to transfer a large amount of data through the ECP interface, checks the data, and counts the errors that occur. The routine for reverse mode evaluation includes the following steps:

- 1. Initialize the host parallel port controller for ECP mode.
- 2. Configure the ECP for reverse data mode to receive data from peripheral.
- 3. When the port receives the first data byte, start the communication timer and initialize the error counter.
- 4. After receiving a predefined number of data bytes from the DSP, calculate the overall data transfer speed and display the error count.

These steps are incorporated in the test routine in Example 6.

Example 6. Host-Side Performance Evaluation Routine

Buffered Transmission

```
void main(){
             unsigned char ch,old_ch;
             int error no=0,i;
             time_t t1,t2;
             long 1;
                    init_ecp();
                                               //Initialize the ECP controller
                                               //Place ECP in Reverse phase
                    init_read();
             while(fifo_empty());
                                               //Wait for ECP FIFO to receive a byte
             old_ch=inb(b_addr+0x400);
                                               //Read that byte
             t1=time(NULL);
                                               //Store the transfer begin time
             for (1=0;1<4096000;1++){
                    while(!fifo_full());
                                               //Wait for ECP FIFO to fill
                    for(i=0;i<16;i++){
                           ch=inb(b addr+0x400);
                                                      //Read a byte
                           if (ch!=old_ch++)
                                                      //Compare with previous value
                                 error_no++;
                                                      //and increment the error counter
                           old ch=ch;
                                                      //if an error occured
             t2=time(NULL);
                                               //Store the transfer end time
             printf("\nErrors=%d",error_no);
                                               //Display the error counter and
             printf("\nSpeed=%f",(double)4096000.0*16.0/(t2-t1)); //transfer speed
}
```

\_

Semiconductor, Inc

đ

eescal

Again, a similar algorithm is employed for the ECP forward mode.

A test system incorporating the programs in Example 5 and Example 6 was run in both forward and reverse mode, yielding results shown in Table 4.

Table 4. ECP Performance Evaluation Results for Single-Byte Transfers

Transfer Direction	Byte Count	Transfer Rate	Error Count
Forward Mode	62.5 Mega	590 KBps	0
Reverse Mode	62.5 Mega	451 KBps	0

The difference between the forward mode and reverse mode transfer rates in Table 4 is due to the fact that the reverse data routine requires more DSP instruction cycles than the forward data routine.

### 6.2 Buffered Transmission

A second, more practical approach is to implement a buffered-type data transfer through the ECP interface. The code in Example 7 on page 18 is a simple DSP routine for reverse mode that transfers an entire buffer to the host computer. In this example, the 'buffer' variable represents the base address of the data buffer to be sent and the 'buf\_len' variable represents the buffer length. The routine scans the buffer in one-step (word) increments and calls the ECP 'write' routine described in Example 3 on page -14 to send the least significant byte of each word in the buffer to the host. These routines can be interrupted by other asynchronous events such as timer interrupts, serial, or DMA transfers, etc.

Send_	Buffer		
	move do	<pre>#buffer,r0 #buf_len,loop_sb</pre>	;Initialize pointer to the start of the buffer. ;Initialize the Loop Counter (LC) Register with ;;buffer length.
loop_	move bsr sb rts	x:(r0)+,a0 write	Prepare the current data word (24-bits) to be sent. ; Send the 8 least significant bits of A0 register.

Example 7. DSP-Side Performance Evaluation Routine—Buffer Transfer, Reverse Mode

In the same manner, one can easily implement the corresponding 'Receive\_Buffer' routine on the DSP using the 'read' routine described in Example 2 on page -12.

To transfer 16-bit words, the 'Send\_Buffer' routine can be modified as shown in Example 8. Similar modifications can be used for forward transfers, and to send or receive 14-bit words.

Example 8. 16-bit Word Buffer Send Routine

Send	_Buffer_2	16	
	move do	#buffer,r0 #buf_len,loop_sb	
	move bsr extract	x:(r0)+,a0 write #\$8008,a,a	; Replace the 8 least significant bits in A0 with the ;; next 8 more significant ones, to be used further ;; by `write'.
100p	bsr _sb rts	write	

## 7 Boosting Performance with a DMA Controller

The performance of an ECP-based communication system can be substantially enhanced by incorporating a dedicated ECP controller with a DMA interface into the DSP56300-based system. A typical connection of a DMA-capable ECP controller (such as the PPC34C60 from Standard Microsystem Corporation or the W91284PIC from Warp Nine Engineering) to a DSP56300 family processor is shown in Figure 8.

Because of an order from the United States International Trade Commission, BGA-packaged product lines and part numbers indicated here currently are not available from Freescale for import or sale in the United States prior to September 2010: DSP56303

#### ECP Standard Parallel Interface for DSP56300 Devices For More Information On This Product, Go to: www.freescale.com



Figure 8. Typical Connection of an ECP Controller to the DSP563xx

As the master of the ECP data link, the host computer uses the ECP control lines to select the type of data transfer (forward or reverse) and initiates the transactions. Thus, the ECP Controller always initiates the DMA cycles with the DSP by asserting DMAREQ (DMA transfer request) and DMADIR (direction of the transfer). The actual DMA transfer begins when the DSP asserts DMAACK (DMA transfer acknowledge) and  $\overline{CS}$ . The DMA transaction ends when the DSP asserts the TC (terminal count) signal.

On the DSP side, some preliminary configuration and initialization is required to perform DMA transactions with the ECP controller, including the following steps:

- Port A Data lines are used for data transfers.
- Port A Address lines specify the location of the transferred data. •
- Port A  $\overline{RD}$  and  $\overline{WR}$  signals command the read and write cycles, respectively.
- Port A AA<sub>x</sub> (One of the four Address Attribute 0:3 lines functions as the chip select signal for the • ECP controller.
- Interrupt line  $\overline{IRQ}_x$  serves as the DMA request signal from the ECP controller. •
- An interrupt handler for the DMA request is installed.
- Three HI08 (Port B) signals are configured as GPIO to function as follows:
  - DMAACK (output)
  - DMADIR (input)
  - TC (output)

When the host initiates an ECP reverse data cycle, (i.e., reads a data buffer from the DSP), the following steps are executed:

- 1. Host configures the ECP controller and initiates the ECP reverse data cycles.
- 2. ECP controller asserts DMAREO.
- 3. The DSP interrupts the execution of its current program and handles the corresponding interrupt as follows:

đ

**COSCO** 

#### Boosting Performance with a DMA Controller For More Information On This Product. Go to: www.freescale.com

- a) Reads the DMADIR to determine the direction of data transfer.
- b) Prepares the data buffer to be sent.
- c) Configures the on-chip DMA controller with the start address of the data buffer and the total number of data words.
- d) Starts the DMA transfer and asserts DMAACK.
- 4. DSP resumes the current program execution while the DMA transfer is performed in parallel.
- 5. When the buffer is transferred, the on-board DMA controller issues an internal interrupt.
- 6. The DSP interrupted to assert TC (end of DMA transfer) and reset the internal DMA controller.
- 7. DSP resumes the execution of the current program.

A similar operation is executed for an ECP forward data cycle initiated by the host.

# 8 Conclusion

The ECP interface enables medium to high-speed parallel data transfers between a host computer and a DSP-based application without the physical limitations of a direct connection between the data buses of the host and DSP. This solution is easy to implement, requiring little or no additional hardware beyond the standard DB25 parallel connector and minimal software development. System performance can be enhanced by using DMA transfers between the host ECP controller and the DSP.

Because of an order from the United States International Trade Commission, BGA-packaged product lines and part numbers indicated here currently are not available from Freescale for import or sale in the United States prior to September 2010: DSP56303

# 9 About the Authors

Mihai V. Micea is a lecturer at the Computer Software and Engineering Department at the Politehnica University of Timisoara, and Executive Director of the DSP Applications Lab Timisoara (DALT) sponsored by Digital DNA from Freescale.

Dan Chiciudean and Lucian Muntean are students at the Automation and Computer Science Faculty at the Politehnica University of Timisoara, and members of the research and development team at DALT.

Contacts:

- micha@dsplabs.utt.ro
- http://dsplabs.utt.ro/dalt/

# 10 References

[1] DSP56300 Family User's Manual (order number DSP56300FM/AD), Motorola, Incorporated, 1999.

[2] DSP56303EVM User's Manual (order number DSP56303EMUM/AD), Motorola, Incorporated, 1999.

[3] DSP56307EVM User's Manual (order number DSP56307EVMUM/D), Motorola, Incorporated, 1999.

[4] *DSP5630x Port A Programming, Application Note* (order number AN1751/D), Motorola, Incorporated, 1999.

[5] Motorola DSP Assembler Reference Manual, Motorola, Incorporated, 1996.

[6] *IEEE Standard Signaling Method for a Bidirectional Parallel Peripheral Interface for Personal Computers*, Draft D1.1, November 5, 1999, Institute of Electrical and Electronic Engineers, Inc.

[7] Extended Capabilities Port: Specifications, Revision 1.06, July 14, 1993, Microsoft Corporation.

[8] *Interfacing the PC. Interfacing the Extended Capabilities Port*, Craig Peacock, February 28, 2000, Internet Resource.

[9] *W91284PIC. IEEE 1284 Peripheral Interface Controller. Data Sheet*, Revision 4.00, 29 October, 1999, Warp Nine Engineering.

[10] *High Performance ECP/EPP Printer Interface Using the PPC34C60 PPIC*, Jeffrey C. Dunnihoo, Application Note 4.17, Revision 13 January, 1994, Standard Microsystems Corporation.